


# Edge Illuminated AC LED AOR Sign



## Features

- Dimensions: 9 1/2" x 9 1/2"
- Adjustable angle - wall, ceiling, sloped ceiling, or side mount
- .3" thick acrylic, with aluminum frame
- Mounting fits standard electrical box with a 4 1/4" x 5 1/4" wall flange
- 120-277 VAC operation
- International symbol of accessibility
- 3/4" lettering height
- Follows ICC A117 visual guidelines for ADA compliance
- Custom signs available upon request

This edge-lit sign fulfills the requirements of NFPA and IBC for an illuminated sign to designate the area of refuge.

## Specifications

This sign may be run off 120 or 277 VAC with an integrated battery back up with 3 hours of light, after loss of the emergency lighting circuit. It shall mount to a standard electrical box with an adjustable angle for wall, ceiling, sloped ceiling, or side mounting. It shall be constructed of fire-retardant aluminum housing with charging indicator and test button, and edge-lit acrylic panel with arrow decals. Clear acrylic relief cut sign area shall measure 6.6" x 11".

## Ordering Information

P/N#	Description
SBSIGN2-ELG120	Edge Illuminated AC LED Sign (Green)
SBSIGN2-ELR120	Edge Illuminated AC LED Sign (Red)